

TRACKED RADIAL FEEDER STACKER

The newly designed 8048SFR is Tesabl's latest offering as a feeder stacker. It comprises of a large feeder hopper that transfers material onto an 80ft conveyor, all fitted to a slew ring assembly allowing for full 360° radial. Designed to allow operators to stockpile/transfer material it eliminates double handling of materials. Its maneuverability makes this unit very versatile and makes it ideal for barge loading and unloading, rail loading / unloading and stockpiling, the ability to move parallel enables the operator to maneuver the unit parallel to the vessel meaning the machine can crab alongside.

The unit can also be compacted for transport on one low loader for easy site to site transport.

FEATURES & BENEFITS

- 100KW (127HP) engine
- Hydraulic folding heading section for transport minimizing setup time
- Hydraulically adjustable discharge height up to 6.5m
- 4m tracks for superior maneuverability and stability
- Fuel efficient Hydraulics system
- User Friendly Hydraulic Controls
- Dual hydraulic main drive system
- Hopper extensions increasing capacity

FEEDER STACKER





D	ED	EO	DM	IAN	CE	CDEC	EIC	ATION
г		ГУ		IV = N	GE 3) F E C I		AIIVN

* Depending on application

DIMENSION SPECIFICATION*

* Depending on material density and set-up

Production Rate*	Engine	Weight	Hopper Capacity
up to 880 TPH	100kW (127Hp)	27500kg Approx. (60,271 lbs)	13 m³ (17 Yd³)

	TRANSPORT DIMENSIONS	MAX WORKING		
Height	Width	Length	Length	Height
3.4m (11'-1")	3.2m (10'-6")	19.4m (63'-7")	26.3m (86'-4")	10m (32'-5")

