



**ID #** 1888

**Naziv:** INTERNATIONAL LAGER PPN 70-F4S

**Kategorija:** Prikolice, poluprikolice  
**Brend (marka):** INTERNATIONAL  
**Opis:** Low Platform TRAILER TRUCK LAGER PPN 70-F4S  
Technical data units with 4 axles  
Saddle height 1250 mm  
Height working platifome (blank) 850 mm  
The total length of 13 260 mm  
Overall width 2540 mm  
Length 3910 mm front  
Length 9350 mm working platifome  
The technical capacity of 70000 kg semi  
The technical capacity of 52000 kg Axle Group  
Technical towing capacity cap (King Pin) 18000 kg  
Net weight 10000 kg semi  
Payload (payload) 60000 kg  
Cantilevered extension 2x250 mm  
Wheel sets  
Tecmo axles - 4 x 13 ton air suspension  
drum brakes, 3 and 4 hinge axis,  
First axle lift (optional)  
Tires 245/70 R17, 5 (16 +1 spare)  
Steel Wheel 17.5 x 6.75 ET125  
Towing cap 2 "JOST flange ECE R55, one position  
Chassis HOLLAND, static load capacity of 50 tons  
Electrical system - signaling  
24 V was performed according to ECE R48  
ADR jack 2 x 7-pin and socket system EBS  
chassis  
Derived from strong steel grid  
construction of two levels, composed  
of longitudinal and transverse beams traverse.  
Embedded auxiliary stajne rates in the last  
the semi-trailer (galvanized)  
Blasted steel granulate, PRIMER 2x,  
2K lacquer paint, RAL clients wish

equipment  
Coasters for the wheel  
Tags and labels for ADR  
Expanders for shipping to 3m. (galvanized)  
Brake installation  
EBS KNORR-E (ABS 2S/2M), PREV, RSS, PEM  
Pneumatic, gabled, salt EEC system  
Pneumatic parking brake  
Nailazna ramp (optional)  
Portable aluminum smoke. 2000x495 mm  
Weight 70 kg piece  
Capacity 33000 kg for a pair (a pair = 2 pieces)  
warranty  
Warranty period 1 year or 100,000 kilometers traveled  
DEMO MODEL - NOVO!!!

**Napomena:**

**Oprema:**

NISKONOSEĆA POLUPRIKOLICA LAGER PPN 70-F4S  
Tehnički podaci poluprikolice sa 4 osovine  
Visina sedla 1250 mm  
Visina radne platforme (prazno) 850 mm  
Ukupna dužina 13260 mm  
Ukupna širina 2540 mm  
Dužina prednjeg dijela 3910 mm  
Dužina radne platforme 9350 mm  
Tehnička nosivost poluprikolice 70000 kg  
Tehnička nosivost grupe osovina 52000 kg  
Tehnička nosivost vučnog čepa (King Pin) 18000 kg  
Neto težina poluprikolice 10000 kg  
Korisni teret (nosivost) 60000 kg  
Konzolno proširenje 2x250 mm  
Osovinski agregati  
Osovine TECMA - 4 x 13 tona zračno ogibljenje,  
doboš kočnice, 3. i 4. osovina zakretna,  
1. osovina podizna (opcija)  
Gume dimenzija 245/70 R17,5 (16+1 rezervna)  
Čelični naplatak 17,5 x 6,75 ET125  
Vučni čep 2" JOST sa priрубnicom ECE R55, jedan položaj  
Stajni trap HOLLAND, statičke nosivost 50 tona  
Elektroinstalacija - signalizacija  
24 V izvedena prema ECE R48  
ADR utičnica 2 x 7-polna i utičnica EBS sustava  
Šasija  
Izvedena od jake čelične rešetkaste  
konstrukcije iz dva nivoa, sastavljena  
od podužnih nosača i poprečnih traverzi.  
Ugrađene pomoćne stajne stope u zadnjem  
dijelu poluprikolice (pocinčane)

Pjeskareno čeličnim granulatom, PRIMER 2x,  
lakirano 2K boja, RAL po želji naručioca

Oprema

Podmetači za točkove

Oznake i listice opasnosti po ADR-u

Proširivači za utovar do 3m. (pocinčani)

Kočiona instalacija

KNORR EBS-E (ABS 2S/2M), PREV, RSS, PEM

Pneumatska, dvovodna, jednokružni sustav EEC

Parkirna pneumatska kočnica

Nailazna rampa (opcija)

Prenosna aluminijska dim. 2000x495 mm

Težina 70 kg komad

Nosivost za par 33000 kg (par = 2 komada)

Garancija

Garantni rok 1 godina ili pređenih 100.000 kilometara  
Posušje, Bosna i Hercegovina

**Lokacija:**

**God. proizvodnje:**

2011





