



ID # 1888

Naziv: INTERNATIONAL LAGER PPN 70-F4S

Kategorija: Prikolice, poluprikolice
Brend (marka): INTERNATIONAL
Opis: Low Platform TRAILER TRUCK LAGER PPN 70-F4S
Technical data units with 4 axles
Saddle height 1250 mm
Height working platifome (blank) 850 mm
The total length of 13 260 mm
Overall width 2540 mm
Length 3910 mm front
Length 9350 mm working platifome
The technical capacity of 70000 kg semi
The technical capacity of 52000 kg Axle Group
Technical towing capacity cap (King Pin) 18000 kg
Net weight 10000 kg semi
Payload (payload) 60000 kg
Cantilevered extension 2x250 mm
Wheel sets
Tecmo axles - 4 x 13 ton air suspension
drum brakes, 3 and 4 hinge axis,
First axle lift (optional)
Tires 245/70 R17, 5 (16 +1 spare)
Steel Wheel 17.5 x 6.75 ET125
Towing cap 2 "JOST flange ECE R55, one position
Chassis HOLLAND, static load capacity of 50 tons
Electrical system - signaling
24 V was performed according to ECE R48
ADR jack 2 x 7-pin and socket system EBS
chassis
Derived from strong steel grid
construction of two levels, composed
of longitudinal and transverse beams traverse.
Embedded auxiliary stajne rates in the last
the semi-trailer (galvanized)
Blasted steel granulate, PRIMER 2x,
2K lacquer paint, RAL clients wish

equipment
Coasters for the wheel
Tags and labels for ADR
Expanders for shipping to 3m. (galvanized)
Brake installation
EBS KNORR-E (ABS 2S/2M), PREV, RSS, PEM
Pneumatic, gabled, salt EEC system
Pneumatic parking brake
Nailazna ramp (optional)
Portable aluminum smoke. 2000x495 mm
Weight 70 kg piece
Capacity 33000 kg for a pair (a pair = 2 pieces)
warranty
Warranty period 1 year or 100,000 kilometers traveled
DEMO MODEL - NOVO!!!

Napomena:

Oprema:

NISKONOSEĆA POLUPRIKOLICA LAGER PPN 70-F4S
Tehnički podaci poluprikolice sa 4 osovine
Visina sedla 1250 mm
Visina radne platforme (prazno) 850 mm
Ukupna dužina 13260 mm
Ukupna širina 2540 mm
Dužina prednjeg dijela 3910 mm
Dužina radne platforme 9350 mm
Tehnička nosivost poluprikolice 70000 kg
Tehnička nosivost grupe osovina 52000 kg
Tehnička nosivost vučnog čepa (King Pin) 18000 kg
Neto težina poluprikolice 10000 kg
Korisni teret (nosivost) 60000 kg
Konzolno proširenje 2x250 mm
Osovinski agregati
Osovine TECMA - 4 x 13 tona zračno ogibljenje,
doboš kočnice, 3. i 4. osovina zakretna,
1. osovina podizna (opcija)
Gume dimenzija 245/70 R17,5 (16+1 rezervna)
Čelični naplatak 17,5 x 6,75 ET125
Vučni čep 2" JOST sa priрубnicom ECE R55, jedan položaj
Stajni trap HOLLAND, statičke nosivost 50 tona
Elektroinstalacija - signalizacija
24 V izvedena prema ECE R48
ADR utičnica 2 x 7-polna i utičnica EBS sustava
Šasija
Izvedena od jake čelične rešetkaste
konstrukcije iz dva nivoa, sastavljena
od podužnih nosača i poprečnih traverzi.
Ugrađene pomoćne stajne stope u zadnjem
dijelu poluprikolice (pocinčane)

Pjeskareno čeličnim granulatom, PRIMER 2x,
lakirano 2K boja, RAL po želji naručioca

Oprema

Podmetači za točkove

Oznake i listice opasnosti po ADR-u

Proširivači za utovar do 3m. (pocinčani)

Kočiona instalacija

KNORR EBS-E (ABS 2S/2M), PREV, RSS, PEM

Pneumatska, dvovodna, jednokružni sustav EEC

Parkirna pneumatska kočnica

Nailazna rampa (opcija)

Prenosna aluminijska dim. 2000x495 mm

Težina 70 kg komad

Nosivost za par 33000 kg (par = 2 komada)

Garancija

Garantni rok 1 godina ili pređenih 100.000 kilometara
Posušje, Bosna i Hercegovina

Lokacija:

God. proizvodnje:

2011





